

BRA-POA 75G



· 轮架:


采用钢压制成型。螺栓轮轴。镀锌，蓝色钝化，不含六价铬。

· 单轮:

· 轮胎/胎面: 采用优质耐冲击尼龙

6，滚动阻力和旋转阻力很小，便于在光滑地面上行走，非常耐磨。

· 轮辋/轮体:-



Technical data

单件重量	0.134 kg
顶板直径	43 mm
总高度 (H)	98 mm
承载能力	75.00 kg
轮宽 (T2)	23 mm
轮径 (D)	75 mm
最低耐温性	-25° C - +80° C ° C
最高耐温性	80° C
胎面及轮胎硬度	70 Shore D
轴承种类	滑动轴承
顶板尺寸 (A, B)	43 mm
螺栓孔径 (d)	11 mm
制造商	Blickle

滚动阻力	■ ■ ■ ■ ■
行走噪音	■ ■ ■ ■ ■
保护地面	■ ■ ■ ■ ■

变量

☐		带插栓 直径 11 x 30.5 -ES
☐		带螺纹杆 M10 x 30 -GS10
☐		-ER02
☐		-ER03
☐		-ER04
☐		-ER05
☐		-EV02
☐		-EV03
☐		-EV04
☐		-EV05
☐		-EV07
☐		Metal expander fitting -E01
☐		Metal expander fitting -E02
☐		Metal expander fitting -E03
☐		Metal expander fitting -E04
☐		Metal expander fitting -E05
☐		-E07

